

EASY CRIMP N

Pneumatic stapler



EASY CRIMP N is a simple, portable, economical and safe pneumatic crimping tool for pre-insulated insulation. It is equipped with plexiglass protections which guarantee a safe during use. It is supplied with a pneumatic pedal and connecting pipes between this and the crimper. It has the possibility of regulating the crimping speed via a valve located on the machine side.

EASY CRIMP N allows the supply of:



- Pre-insulated ferrules with various shapes of metal crushing on the copper side
(from 0.5 to 50 mm²)



- Pre-insulated terminals, faston, eyelets, forks etc. with plastic crushing on the copper side



EASY CRIMP N has the possibility to easily interchange the crimping crimpers.

You can find the related video on www.mgrelectro.it

A25J 0.5-2.5mm ²	A30J 0.5-6mm ²	A30JC 1.0-6mm ²	A40J 0.25-6mm ²	A03C 0.5-6mm ²	A06WF2C 0.5-2.5mm ²
AMC4 2.5, 4, 6mm ²	A07FL 1.25-2.5mm ²	A08FL 1.5-6.0mm ²	A056FL 0.5-2.5mm ²	A10WF 0.25-10mm ²	A04WFL 0.5-4mm ²
A26TW 2x0.5-6mm ²	A16WF 4-16mm ²	A056FL 4.8-6.3mm ²	A625GFL 6-25mm ²	A35WF 10-35mm ²	A03B 1.5-6mm ²
A03BC 0.5-6mm ²	A1016 0.5-16mm ²	A10 1.5-6mm ²	A10A 0.5-10mm ²	A101 1.5-10mm ²	A05D 0.14-4mm ²
A02H 8.0mm/6.4mm 1.7mm/1.0mm	A02H2 6.5mm/5.4mm 1.7mm	A05H 4.5mm/6.5mm/7.0mm 1.7mm/1.0mm	A02H1 8.8mm/8.1mm 6.5mm	A457 5.4mm/8.0mm 11.0mm ²	A0616WFL * 6, 10, 16mm ²
A0510 * 0.5-10mm ²	A5516 * 5.5-16mm ²	A1HK * 2mm/2.2mm/2.4mm ²	A2HK * 0.5-4mm ²	A3HK * 4-10mm ²	A1050 * 10A-50A

Crimping range (mm ²)	Terminal Supplier
Ferrules, 0.25~35mm ²	
Twin ferrules, 2×0.5, 1.0, 1.5, 2.0, 2.5, 4, 6, 10, 16mm ²	
Insulated O type or Y type terminals, 1.0, 2.0, 2.5, 4.0, 6.0mm ²	
Non-insulated O type or Y type terminals, 0.5, 1.0, 1.5, 2.0, 2.5, 4.0, 6.0, 10mm ²	
Males or females receptacles, 1.0, 2.0, 2.5, 4.0, 6.0mm ²	
Contact pin for rectangular connector, 1.0, 2.0, 4.0mm ²	